

## Dual Fuel Construction Heaters

Model	F-400T	F-1000T	F-1500T
<b>Fuel</b>	Propane or Natural Gas	Propane or Natural Gas	Propane or Natural Gas
<b>BTU/hr</b>	400,000 btuh	1,000,000 btuh	1,500,000 btuh
<b>Low Fire BTU/hr</b>	N/A	N/A	650,000 btuh
<b>Inlet Pressure (Propane)</b>	11" W.C. MAX	11" W.C. MAX	11" W.C. MAX
<b>Inlet Pressure (Natural Gas)</b>	4.0" W.C. MIN	4.0" W.C. MIN	4.0" W.C. MIN
<b>Power Requirement</b>	115V/60Hz/1Ph/15amp	115V/60Hz/1Ph/20amp	115V/60Hz/1Ph/20amp
<b>Fan Motor</b>	1/3 HP	1 HP	1 HP
<b>Air Circulation</b>	2,000 CFM	7,000 CFM	7,000 CFM
<b>Ignition</b>	Direct Spark Control	Direct Spark Control	Direct Spark Control



<b>Thermostat Control</b>	Yes	Yes	Yes
<b>L x W x H</b>	48" x 22" x 24"	61" x 29" x 38"	61" x 29" x 38"
<b>Air Outlet</b>	15" Diameter	26" Diameter	26" Diameter
<b>Weight</b>	90 lbs	356 lbs	360 lbs

## Required Equipment for Heater Installations

<b>Recommended For Model No.</b>	<b>Second Stage Regulator</b>	<b>Typical Hose Assembly</b>
<b>F-400T</b>	B42RO.75 (3/4" NPT)	S52180-12 3/4" x 15ft Hose Assembly
<b>F-1000T</b>	B42R1.25 (1-1/4" NPT)	S54180-20 1-1/4" x 15ft Hose Assembly
<b>F-1500T</b>	B31R1.25 (1-1/4" NPT)	S54180-20 1-1/4" x 15ft Hose Assembly