



Free Quotes Call Today!
(877) 736-5169

Electric Heaters

QUIET, FLEXIBLE AND DEPENDABLE ELECTRIC HEAT FOR ANY JOB

Permanent cleanable inlet filters prevent particulates at jobsite from contaminating heating element and controls. Fan speed inverter control provides optimum temperature rise by adjusting blower.

Convenient colour coded cam lock power connections for easy installation. Simplified control panel design allows for easy operations at 60kw, 40kw & 20kw inputs.

Air flow and high temperature indication lights incorporated on recessed control panel.

Optional Remote Thermostat C.W 25 ft cord

HEAT SETTING	60kw	40kw	20kw	Fan Only
BTUH	205,000 btuh	137,000 btuh	68,000 btuh	
CFM	3300 cfm	2800 cfm	2450 cfm	3900 cfm
Temperature Rise	110°F/43°C	85°F/30°C	50°F/10°C	
Noise Rating	67 db	63 db	63 db	71 db
Electric Supply	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available

Static Pressure	1/2" W.C.	1/2" W.C.	1/2" W.C.	an Only
Motor / Blower	1 1/2 HP - Belt Drive	1 1/2 HP - Belt Drive	1 1/2 HP - Belt Drive	1 1/2 HP - Belt Drive
Dual Air Inlet Outlet	16" x 16" Inlet 18" x 13" Outlet 20" Ductable return and supply	16" x 16" Inlet 18" x 13" Outlet 20" Ductable return and supply	16" x 16" Inlet 18" x 13" Outlet 20" Ductable return and supply	16" x 16" Inlet 18" x 13" Outlet 20" Ductable return and supply
L x W x H	32" x 48" x 25.5"	32" x 48" x 25.5"	32" x 48" x 25.5"	32" x 48" x 25.5"
Weight	290 lbs	290 lbs	290 lbs	290 lbs

Approval CSA & ESA for Indoor and Outdoor Use

HEAT SETTING	150 KW	90 KW	60 KW	Fan Only
BTUH	512,000 btuh	307,000 btuh	205,000 btuh	
CFM	6300 cfm	5800 cfm	4600 cfm	6800 cfm
Temperature Rise	120°F / 49 deg C	88°F / 31 deg C	56°F / 13 deg C	
Noise Rating	83 db	81 db	76 db	85 db
Electric Supply	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available	480 Volt or 575 Volt Models Available
Static Pressure	1/2 " W.C.	1/2" W.C.	1/2" W.C.	an Only

Motor / Blower	7-1/2 hp – Direct Drive	7-1/2 hp – Direct Drive	7-1/2 hp – Direct Drive	7-1/2 hp – Direct Drive
Dual Air Inlet Outlet	20" ductable return & supply	20" ductable return & supply	20" ductable return & supply	20" ductable return & supply
L x W x H	66" x 36" x 40"	66" x 36" x 40"	66" x 36" x 40"	66" x 36" x 40"
Weight	560 lbs	560 lbs	560 lbs	560 lbs